



Enterprise



Optics 13°



Optics 25°



Optic 38°



Diffused Lens 110°



Recess



Opt. Dimmer 0-10V Push Dali



Casambi Optional



CRI TYP 97



Opt. Alveolar filter (-20% Lumen flux)

POWER – POWER SUPPLY – CRI

	Ø 800 5 spot 55W 110-230Vac	Ø 1600 10 spot 110W 110-230Vac	Ø 2400 15 spot 165W 110-230Vac	SunLike Ø 800 5 spot 55W 110-230Vac	SunLike Ø 1600 10 spot 110W 110-230Vac	SunLike Ø 2400 15 spot 165W 110-230Vac
2700 K	4820 lm	9640 lm	14460 lm	4235 lm	8470 lm	12705 lm
3000 K	5050 lm	10100 lm	15150 lm	4370 lm	8740 lm	13110 lm
4000 K	5200 lm	10400 lm	15600 lm	4560 lm	9120 lm	13680 lm

LUMINOUS FLUX
CRI 80 disponibile solo per progetti custom. Nella versione CRI 80 sommare 38% ai dati sopra riportati.
CRI 80 available only for custom project. With CRI 80 add 38% on above lumen flux.



Per ogni spot predisporre un foro Ø 75 mm.
(Consultare istruzioni montaggio).

For each spot provide Ø 75 mm hole.
(Check installation manual).



Alluminio Verniciato
Painted Aluminum

Finitura nero opaco.
Finishing matt black.

